

SINGLE COLOR DOSER / DOZAJLAMA ÜNİTESİ (TEKLİ)



SRC-CM

- With the function of permanent memory and storage.
- Use of brushless DC-motor, no need for maintenance.
- Use of micro-computer control, intelligentize to calculate accurately.
- Can satisfy the requirement of external signal input at the same time.
- The screw is handled with chrome to be durable.
- The modular structure is easy to assemble&disassemble, clean and exchange.

- Single color dose mixer's standard base equips hopper magnets to attract metal to protect the destroying of screw in injection machines .
- The stirrer is optional for single color does mixer, and should matched with stirrer controller to mix the material even.
- The double color dose mixer equips base with stirrer, can satisfy the request of mixing double materials .
- The main material hopper is standard equipment for double color dose mixer, optional for single color dose mixer.

Model/ Model	Unit/ Ünite	SRC-CM-12S	SRC-CM-14S	SRC-CM-16S
Output Capacity/ Çıkış Kapasite	kg/h	0.3~3	0.5~5	0.8~10
Motor Power/ Motor Güç	W	50	50	50
Rotating Speed/ Dönme Hızı	rpm	0~3000	0~3000	0~3000
Storage Capacity/ Depolama Kapasitesi	L	10	10	10
Reduction Ratio/ Azaltma Oranı		30:1	30:1	30:1
Screw Diameter/ Vida Capı	mm	12	14	16
Dimensions/ Ölçüler				
H/Y	mm	520	520	520
W/G	mm	590	590	590
D/D	mm	355	355	355
Net weight/ Net ağırlık	kg	16	16	16

Note: We reserve the right to make changes in the specifications contained in this document without prior notification.

VERTICAL COLOR MIXER / DİKEY RENK KARIŞTIRICI MİKSERİ



SRC-SB

- Double-layer stainless steel, vertical design fast and even stirring.
- Dismountable beater, stainless steel stirring room to facilitate cleaning.
- Directly driven by the motor and high stirring efficiency.
- Vertical design, less land occupied, easy dismounting.
- Automatic stop device, automatic stop in 0-30 minutes can be set.
- Multi safety protection device to ensure the operator safe.

Model/ Model	Motor Power/ Motor Güçü	Capacity/ Kapasite	Power/ Güç	Mix Type/ Karıştırma Tipi	Dimensions/ Ölçüler (L*W*H/ U*G*Y)	Net Weight/ Net Ağırlık
	Kw	(Kg)	(V)		(mm)	(Kg)
SRC-SB-50	1.5	50	AC3 50/60Hz	Vane Type/ Kanat Tipi	830x830x1120	130
SRC-SB-100	3	100	AC3 50/60Hz		1000x1000x1280	190
SRC-SB-150	4	150	AC3 50/60Hz		1130x1130x1380	250
SRC-SB-200	5.5	200	AC3 50/60Hz		1200x1200x1500	320

Note: We reserve the right to make changes in the specifications contained in this document without prior notification.